




## USB2.0 Web Conference Camera



	HD652	HD653
<b>Sensor</b>	1/2.7" HD color CMOS	1/2.7" HD color CMOS
<b>Effective Pixel</b>	2.1 Megapixel	2.1 Megapixel
<b>Min Illumination</b>	5.0Lux at F2.0	5.0Lux at F2.0
<b>White Balance</b>	Auto	Auto
<b>Gain Control</b>	Auto	Auto
<b>Back Light Compensation</b>	N/A	N/A
<b>Electronic Shutter</b>	1/30	1/30
<b>SN Ratio</b>	>50db	>50db
<b>Focus</b>	4mm	f=3-10mm
<b>Iris</b>	fixed	fixed
<b>Zoom</b>	Fixed Lens	3x Zoom
<b>HOV</b>	82.5°	70° - 30°
<b>Video Output Interface</b>	USB2.0	USB2.0
<b>Video Output Format</b>	MJPEG: 1080p@30, 720p@30	MJPEG: 1080p@30, 720p@30

### Product Parameters

<b>Communication Interface</b> EIA/RS232C,RS485(Bidirectional) USB	<b>OSD Menu</b> No Support	<b>Pan Movement Speed</b> 360° Continuously Pan movement, 1-60°/S	<b>Power Supply</b> DC12V, 1.2A
<b>Communication Protocol</b> VISCA, PELCO-D	<b>Image Flip</b> Support	<b>Tilt Movement Speed</b> -30° ~ +90°, 1-60°/S	<b>Work Temperature</b> 0-50°C
<b>Baud Rate</b> 9600/38400bps	<b>Speed Match</b> Support	<b>Boundary Scanning</b> 0-359°(programmable)	<b>Work Humidity</b> 0-95%RH
<b>Preset Position</b> 64		<b>Auto Pan Scanning</b> Support	<b>Dimension(LxWxH)</b> 124mmX120mmX145mm
<b>Touring Line</b> 4 cruise Sequence		<b>Remote Controller</b> IR Wireless Remote Controller P/T/Z	<b>Weight</b> 800g